

BLACK ZINC AEROSOL

SECTION 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Black Zinc Aerosol 400ML
Product Use: Enamel Paint Coating With Zinc For Bare Metal.
Supplier: Vertex Lubricants NZ
22 Marphona Crescent
Takanini 2105
Phone: 09/640 0004
Email: info@vertexlubricants.co.nz
Emergency Number: 0800 764 766 (0800 POISON) National Poison Centre
Issue Date: 4 September 2024 and is valid for 5 years from this date.

SECTION 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.
Classified as dangerous goods for transport purposes.

HSNO Classifications:

2.1.2A Flammable Aerosol
6.3A Irritating to the skin
6.4A Irritating to the eye
6.7B Suspected human carcinogen
6.8B Suspected human reproductive or developmental toxicant
6.8C Toxic human reproductive or developmental effects via lactation
6.9B Harmful to human target organs or systems (Single exposure)
9.1B Ecotoxic in the aquatic environment with long effects (Chronic)
9.3C Harmful to terrestrial vertebrates

GHS Classifications:

Aerosol Category 1
Skin Irritation Category 3
Eye Irritation Category 2
Carcinogenicity Category 2
Reproductive Toxicity Category 2
Reproductive Toxicity Effects Via Lactation
STOT (single exposure) Category 2
Aquatic Toxicity Category 2
Hazardous to Terrestrial Vertebrates



Signal Words: Danger

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 May cause serious eye irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H362 May cause harm to breast fed children.
H371 May cause damage to organs by inhalation or if swallowed.
H411 Toxic to aquatic life with long lasting effects.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.

© Vertex is a registered trademark of Lubricants NZ Ltd.

H433 Harmful to terrestrial vertebrates

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Acetone	67-64-1	30 - 60
Xylene	1330-20-7	10 - 30
Aromatic Hydrocarbon	64741-95-6	< 10
Hydrocarbon Propellant (LPG, Butane, Propane)	68476-85-7	10 - 30
Non-hazardous ingredients		To 100

SECTION 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get to hospital or doctor without delay.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.

Inhalation: IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

Ingestion: IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.

Notes to physician: Treat symptomatically and supportively. No specific antidote.

SECTION 5 – FIRE FIGHTING MEASURES

General fire hazards: Pressurised aerosol container. Extremely flammable aerosol.

Specific hazards: Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float and be re-ignited on surface water. Will burn if involved in a fire.

Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.

Extinguishing media: For small fires: use dry chemical, carbon dioxide, water spray or alcohol resistant foam.
For large fires: Use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing water into the aquatic environment.
Do NOT use straight streams of water.

Protective equipment: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighting instructions: In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.

Hazchem Code: 2YE

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- Minor spills:** Clean up all spills immediately. Remove all sources of ignition. If safe to do so, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.
- Major spills:** Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers for disposal.

SECTION 7 – HANDLING AND STORAGE

- Handling** Read product label before use. Keep out of reach of children.
- Precautions:** This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container. Do not pierce or burn, even after use. Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling. Beware: deliberately sniffing or inhaling concentrated contents can be harmful or fatal.
- Storage:** Protect from Sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well-ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Exposure Limits:** No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Acetone	1,185	2,375
Xylene	217	-
LPG (butane, propane)	1,800	-

- Additional Information:** Wash hands before eating, drinking and smoking.
- Engineering Controls:** No controls required when handling small quantities. Use outdoors or with adequate ventilation. Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion-resistant.
- Protective Equipment:** General protective gloves are recommended. In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. In case of inadequate ventilation wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- Physical state:** Black Spray with a solvent odour
- pH:** Not applicable
- Vapour Density:** > 1 (Air =1)
- Vapour Pressure, kPa:** 300 - 600

Boiling Point, °C:	Not applicable.
Melting Point, °C:	Not applicable.
Specific Gravity:	Not applicable.
Flash Point, °C:	<0 (propellant)
Explosion Limit, % v/v:	LEL 1.2% UEL 9.5%
Autoignition Temp, °C:	Not applicable.
Solubility:	Not soluble in water.

SECTION 10 – STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.
------------	--

SECTION 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.
Acute Oral Toxicity:	LD ₅₀ estimated to be > 3,470 mg/kg (based on component mixture, excluding propellant).
Acute Dermal Toxicity:	LD ₅₀ estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).
Acute Inhalation Toxicity:	LC ₅₀ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture, excluding propellant). Beware deliberately sniffing or inhaling concentrated contents may be harmful or fatal.
Skin Irritation:	May cause skin irritation. Prolonged/repeated contact may cause defatting of the skin and dermatitis.
Eye Irritation:	Spray may be irritating to the eye.
Inhalation:	May cause drowsiness or dizziness. Inhalation may cause narcotic effects.
Respiratory Irritation:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Sensitisation:	Product is not expected to be a sensitiser.
Mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Product is a suspected human carcinogen.
Reproductive Toxicity:	Product is a suspected human reproductive or developmental toxicant.
Reproductive Toxicity Effects via Lactation:	Product has toxic human reproductive or developmental effects on or via lactation.
Specific Target Organ Toxicity:	Harmful to human target organs or systems (single exposure).
Repeated Dose Toxicity:	Prolonged contact with product may result in irritant contact dermatitis.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:	Ecotoxic in the aquatic environment with long lasting effects.
Mobility:	Product is partially volatile, and large proportion will rapidly evaporate to the air if released into water.
Persistence /degradability:	More volatile components are expected to degrade in air.
Bioaccumulation Potential:	Some components may be persistent and may bioaccumulate.

SECTION 13 – DISPOSAL CONSIDERATION

- Material Disposal:** Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
- Container Disposal:** Recycle empty container if possible or dispose in landfill. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.

SECTION 14 – TRANSPORT INFORMATION

- Transport:** Classified as a Dangerous Good for transport purposes.
Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.
They may be loaded with Classes 3,6,8,9, foodstuffs and foodstuff empties
- Proper Shipping Name:** Aerosols
- UN Number:** 1950
- Dangerous Goods Class:** 2.1
- Transport Labels Required:** Class 2 Flammable (Land, Sea and Air) EHMS (Sea and Air)
Land, Sea, Air Sea Air
- 

- Subsidiary Risk:** Not applicable
- Packing Group:** Not applicable
- Marine Pollutant:** Yes
- EMS Number:** F-D, S-U (UN 1950 aerosols)
- DG Segregation:** This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

SECTION 15 – REGULATORY INFORMATION

- EPA Approval Number:** HSR002517 Aerosols (Flammable, Carcinogenic) Group Standard 2020.
- Inventory Listing**
SDS regulations NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.
This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.
- EPA Hsno Controls:** Refer to www.epa.govt.nz for information on Controls.
This substance is to be managed using the conditions specified in an applicable Group Standard.

SECTION 16 – OTHER INFORMATION

Additional information: Health effects from exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that the user will assess the risks and apply control methods where appropriate.

Abbreviations	AICS	Australian Inventory of Chemical Substances
	ADG	Australian Code for the Transport of Dangerous Goods
	CAS	Chemical Abstract Service number
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods
	EPA	Environmental Protection Agency
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	LEL	Lower Explosion Limit
	mg/m ³	Milligrams per Cubic Metre
	NZIoC	New Zealand Inventory of Chemicals
	N.O.S.	Not otherwise specified
	OEL	Occupational Exposure Limit
	PEL	Permissible Exposure Limit
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
	UEL	Upper Explosion Limit

Date of issue/Date of revision

Current Version: 5 September 2024

This SDS contains only safety-related information. For other data see product literature.

SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.