



VERTEX MULTI LUBE 7N1 (BULK) MSDS

SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	Vertex Multi Lube 7n1 HD (Bulk)
Product Use:	Fast drying gloss enamel paint aerosol for wood, metal or fibreglass.
Supplier:	Vertex Lubricants NZ
	22 Marphona Crescent
	Takanini 2105
	Phone: 09/640 0004
	Email: info@vertexlubricants.co.nz
Emergency Number:	0800 353 645
Chemical Nature:	Aliphatic Low Aromatic Hydrocarbon, Mineral Oil, Butoxyethanol
Issue Date:	4 September 2024 and is valid for 5 years from this date.

SECTION 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered as a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

Classified as dangerous goods for transport purposes.

GHS Classifications:	HSNO Classifications:	
Flammable Liquids: medium hazard	3.1C	Flammable liquid
Aspiration Hazard Category 1	6.1E	Acutely toxic (aspi

tions:

9.1B

oxic (aspiration) Harmful to human target organs. Narcotic (single) 6.9B

Ecotoxic in the aquatic environment with long lasting effects

STOT (single exposure) Category 3 (Narcotic)

Aquatic toxicity (Chronic) Category 2

٩	$\langle \rangle$	\diamond	
---	-------------------	------------	--

Signal Words: Danger

Hazard Statements

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness if inhaled.

H411 Toxic to aquatic life with long lasting effects.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Aliphatic Low Aromatic Hydrocarbon	64742-82-1	30 - 60
Mineral Oil	8042-47-5	10 - 30
Butoxyethanol	111-76-2	< 10
Other ingredients determined to not be hazardous	-	to 100%

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice. Vertex is a registered trademark of Lubricants NZ Ltd.



Material Safety Data Sheet

SECTION 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE (0800 764 766) or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. Take off all contaminated clothing. Direct contact may cause irritation in sensitive individuals. If skin irritation occurs: Get medical advice.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.

SECTION 5 – FIRE FIGHTING MEASURES

Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may burst. If safe to do so, remove containers from the path of fire. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. May float and be re-ignited on surface water.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self- contained breathing apparatus if risk of exposure to products of combustion. Use water spray to keep fire-exposed containers cool.
Extinguishing media:	Use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Use water spray to cool fire exposed containers. Do NOT use straight streams of water. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment.
Hazchem Code:	ЗҮ

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- Minor spills: Clean up all spills immediately. Remove all sources of ignition. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water.
- Major spills:Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage
from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent
(soil, sand or other inert material). Collect and seal in properly labelled containers for disposal.

SECTION 7 – HANDLING AND STORAGE

- HandlingRead product label before use. Keep out of reach of children. This product is highly flammable. KeepPrecautions:away from heat and open flames/hot surfaces. No smoking. Do not use near an open flame or other
ignition source. Use outdoors or in well-ventilated area. Avoid breathing vapour. Beware: Deliberately
sniffing or inhaling concentrated contents can be harmful or fatal. Wash hands with soap and water after
handling. Avoid release to the environment.
- Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well-ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

www.vertexlubricants.co.nz





SECTION 8 – EXPOSURE CONTROLS AND PEROSNAL PROTECTION

Exposure Limits: No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Aliphatic Low Aromatic Hydrocarbon (supplier)	525	-
Mineral Oil (oil mist)	5	10
Butoxyethanol (skin)	25	-

Additional Information:	Wash hands before eating, drinking and smoking.
Engineering Controls:	No controls are normally required when handling small quantities. Use with adequate ventilation. Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation, lighting and electrical equipment should be explosion-resistant. Use only non-sparking tools. Take precautionary measures against static discharge.
Protective Equipment:	In an industrial environment: gloves, safety glasses or chemical goggles and protective gloves are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. In case of inadequate ventilation wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear, almost colourless liquid.
Odour:	Slight hydrocarbon odour.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	About 0.25 @ 20°C.
Boiling Point, °C:	About 160
Melting Point, °C:	Not applicable.
Specific Gravity:	About 0.80
Flash Point, °C:	About 40
Explosion Limit, % v/v:	LEL 1% UEL 7%
Autoignition Temp, °C:	200
Solubility:	Not soluble in water.

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

SECTION 11 – TOXICOLOGICAL INFORMATION

Basis forInformation given is based on product testing, and/or similar products, and/or components.Assessment:Acute Oral Toxicity: Low toxicity: LD50 of mixture calculated to be > 5,000 mg/kg, Rat.

Vertex Lubricants



Oils // Grease // Coolant // Chemicals



Acute Dermal	Low to visitive LD \sim of mixture colored to be $\gtrsim 2000$ mg/kg. Debbit
Toxicity:	Low toxicity: LD_{50} of mixture calculated to be > 2000 mg/kg, Rabbit.
Acute Inhalation	Low toxicity: LC ₅₀ of mixture calculated to be > 20 mg/L, Rat 4 hours
Toxicity:	
Skin Irritation:	May cause mild skin irritation in sensitive individuals. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
Eye Irritation:	Vapours may be irritating to the eye. Contact with eyes is mildly irritating causing short term discomfort. Avoid contact with eyes.
Respiratory Irritation:	Inhalation of vapour may cause irritation to the nose and throat. Prolonged inhalation of large quantities of vapour will result in moderate discomfort. Symptoms of over-exposure can include disciples and other control pervises system effects.
Sensitisation:	dizziness, nausea, headaches and other central nervous system effects. Not expected to be a sensitiser.
Repeated Dose	Prolonged contact with product may result in irritant contact dermatitis. May cause damage to organs
Toxicity:	through prolonged or repeated exposure.
Mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Not expected to be toxic.
Specific Target Organ Toxicity:	May be harmful to human target organs or systems.
STOT (Narcotic):	Prolonged Inhalation at high concentrations may cause drowsiness or dizziness (narcotic).
Other Health Effects:	Prolonged or repeated exposure to high concentrations may result in temporary hearing loss.
Additional Information:	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:	Product is harmful to aquatic organisms with possible long-lasting effects with continuous exposure.
Mobility:	Floats on water. Highly volatile and will evaporate to air. Some components show low soil mobility.
Persistence/ Degradability:	Expected to be biodegradable. Can rapidly degrade in air. Some components may be persistent.
Bioaccumulation:	Not expected to significantly bioaccumulate.

SECTION 13 – DISPOSAL CONSIDERATION

- Material Disposal: Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
- Container Disposal: Recycle empty container if possible. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.


SECTION 14 – TRANSPORT INFORMATION

Transport:	Classified as a Dangerous Good for transport purposes.
Proper Shipping Name:	HYDROCARBONS, LIQUID, N.O.S.
UN Number:	3295
Dangerous Goods Class:	3



Material Safety Data Sheet

Transport Labels Required: Class 3 Flammable (Land, Sea and Air), EHSM (Sea and Air)



Subsidiary Risk:	Not applicable	
Packing Group:	III	
Marine Pollutant:Yes		
EMS Number	F-E, S-D	

DG Segregation: This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

SECTION 15 – REGULATORY INFORMATION

Inventory Listing SDS regulations	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed. This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.
EPA Approval Number:	HSR002515 Aerosols (Flammable) Group Standard 2020.
EPA Hsno Controls:	Refer to <u>www.epa.govt.nz</u> for information on Controls. This substance is to be managed using the conditions specified in an applicable Group Standard.

SECTION 16 – OTHER INFORMATION

Additional information:	will depend effectivenes that it is im	ts from Exposure: It should be noted that the effects from exposure to this product on several factors including: frequency and duration of use; quantity used; s of control measures; protective equipment used and method of application. Given practical to prepare a report which would encompass all possible scenarios, it is that users will assess the risks and apply control methods where appropriate.
Abbreviations	CAS	Chemical Abstract Service number
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods
	EPA	Environmental Protection Agency
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods
	LC ₅₀	Lethal Concentration, 50% / Median Lethal Concentration
	LD ₅₀	Lethal Dose, 50% / Median Lethal Dose
	LEL	Lower Explosion Limit
	mg/m³	Milligrams per Cubic Metre
	NZIOC	New Zealand Inventory of Chemicals
	N.O.S.	Not otherwise specified
	OEL	Occupational Exposure Limit
	PEL	Permissible Exposure Limit

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice. [®] Vertex is a registered trademark of Vertex Lubricants NZ Ltd.

Vertex Lubricants





STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
TLV	Threshold Limit Value
TWA	Time Weighted Average
UEL	Upper Explosion Limit

Date of issue/Date of revision

Current Version: 4 September 2024

This MSDS contains only safety-related information. For other data see product literature.

MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.