

**AGRI MONO T2 10W****PRODUCT DESCRIPTION**

Agri Mono T2 10W is a Monograde Universal Tractor Transmission Oil (UTTO) specially designed for agricultural hydraulic and hydrostatic systems as well as a wide range of tractor transmissions. Agri Mono T2 is formulated to meet a wide range of specifications reducing the need to carry multiple Tractor Transmission fluids. The product is suitable for use in equipment fitted with wet brakes and can service almost all agricultural hydraulic and hydrostatic transmission systems. High Performance additives provide excellent friction control in brakes, reducing chatter and prolonged service life.

**APPLICATIONS & BENEFITS**

- Suitable for use in a wide range of transmissions, hydraulic systems, and drive trains in agricultural equipment.
- Advanced formulation reduces noise and chatter in wet brake systems.
- Robust Monograde formulation offers less oil shear and extended service life of the oil.
- Wide range of industry specifications reduces the need to carry multiple oils.

**PACK SIZES AVAILABLE**

20L - 200L

**SPECIFICATIONS**

- API GL-4
- Allison C-4
- Caterpillar TO-2
- CNH MAT 3525, 3526, 3505
- Eaton Vickers
- Ford M2C86B, C
- JCMAS HK P-041, P-042
- John Deere J20C, J20D
- Kubota UDT, Super UDT
- Massey Ferguson: M1145
- Parker (Denison) HF-0, HF-1, HF-2
- VCE 1273.03
- Volvo WB101
- White Q-1826
- ZF TE-ML-03E
- ZF TE-ML-03F
- ZF TE-ML-05F
- ZF TE-ML-06E
- ZF TE-ML-06F
- ZF TE-ML-06K
- ZF TE-ML-17E
- ZF TE-ML-21F

**TYPICAL CHARACTERISTICS**

AGRI MONO T2 10W	UNITS	VALUES
VISCOSITY	cSt @ 40°C	32.2
	cSt @ 100°C	5.45
SPECIFIC GRAVITY	@ 15°C	0.869
VISCOSITY INDEX		104
POUR POINT	°C	-30
FLASH POINT	°C	218

### ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.