

AGRI STOU 15W-40**PRODUCT DESCRIPTION**

Vertex Agri STOU 15W40 is a high performance and multifunctional oil (STOU / MFO) utilising advanced mineral technology. Vertex Agri STOU 15W40 is recommended for use in Agricultural Petrol and diesel engines, manual transmissions (including those calling for a GL-4 and SAE 10-W30 / 15-W40) and hydraulic systems and final drives. Advanced frictional properties provide superior performance in wet brake systems, and multi plate differentials. Vertex Agri STOU 15W40 is a multi-functional product and can service a wide range of equipment. Vertex Agri STOU 15W40 can service diesel engines requiring an API CF-4 rated fluid.

APPLICATIONS & BENEFITS

- Versatility – Can be used in various kinds of equipment (tractors, combines, seeding and harvesting equipment, sprayers etc.).
- Helps reduce the list of applied lubricants. The use of a single product type eliminates the risk of incorrect use when servicing and reduces maintenance costs.
- Wear protection - Delivers wear protection of high-load drives, gears, and bearings through stable oil film.
- High thermal stability ensures reliable engine operation over a wide temperature range, extending the lubricants life.
- Stable performance - selected additives and friction modifiers deliver smooth vibration free braking and gearshift, extending component life.
- Superior cleaning and dispersant properties - Prevents engine and other parts from various types of deposits.
- Compatibility with seal materials - good compatibility with sealing materials and non-ferrous metals in all agricultural machinery.

PACK SIZES AVAILABLE

20L - 200L

SPECIFICATIONS

- API CF-4/CE/SL
- ACEA E2
- CMS M 1145
- CMS M 1144
- MB 229.1
- ZF: TE-ML 06B/07B

TYPICAL CHARACTERISTICS

AGRI STOU 15W-40	UNITS	VALUES
VISCOSITY	cSt @ 40°C	106.2
	cSt @ 100°C	14.2
TBN, mg KOH/g		11.2
VISCOSITY INDEX		125
POUR POINT	°C	-24
FLASH POINT	°C	215

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.