

PRODUCT DESCRIPTION

Vertex Ultra Tac is a virgin total loss oil for the lubrication of chainsaw and high-speed machinery. Designed to protect the chain and bar of all types of machinery. Available in ISO 150 and 220. Vertex Ultra Tac is added directly to the chain bar oil reservoir for automatic lubrication systems but can also be used manually on the chain if needed for added lubrication and protection. Vertex Ultra Tac keeps chains sharper for longer and its tacky formula stops it being flung off the chain during operation providing protection over normal engine type oils. It also ensures that the oil feeds at the correct ratio to reduce wastage. Vertex Ultra Tac is designed for all petrol and electric type chainsaws. Its advanced formula and special additive pack reduce wear on the bar, chain, and sprockets. The product also flushes away dust, chips and sap from the working surfaces ensuring smooth and consistent cutting. Its superior formulation lubricates chains and sprockets and provides a barrier against corrosion, moisture & premature wear on the working surfaces.

APPLICATIONS & BENEFITS

- Vertex Ultra Tac is suitable for the following types of chainsaws: Black & Decker - Dolmar - Echo - Hitachi - Homelite - Honda - Husqvarna - John Deere - Kawasaki - Komatsu - Makita - McCulloch - MTD - Ozito Poulan - Ryobi - Shindaiwa - Stihl - Talon - Tanaka and others requiring bar & chain lubrication.
- Vertex Ultra Tac Resists "Throw Off" due to added tackifiers.
- Contains superior extreme pressure additives.
- Odorless.
- Low Misting.
- Excellent resistance to water wash out.
- Exceptional wear protection.
- Prevents corrosion.
- Suitable for central lube systems or applied directly neat.
- Vertex Ultra Tac 150 is especially developed to lubricate the chains of chain saws to prevent them from breaking or jamming.

PACK SIZES AVAILABLE

20L - 200L - 1000L IBC

TYPICAL CHARACTERISTICS

ULTRA TAC	UNITS	150	220
VISCOSITY	cSt @ 40 °C	150	220
	cSt @ 100 °C	14.8	22
VISCOSITY INDEX		98	106
POUR POINT	°C	-15	-14
FLASH POINT	°C	<240	<240

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.