



EXPERT GT 15W-40

PRODUCT DESCRIPTION

Vertex Expert GT 15W-40 is a premium quality multi grade gasoline engine oil formulated with select base oils and advanced additives to deliver outstanding engine performance and protection for today's gasoline engine powered cars and trucks. It meets the performance requirement of API SP and provides superior piston cleanliness, wear protection, fuel efficiency and prolonged engine life.

APPLICATIONS & BENEFITS

- Meets API SP.
- Multigrade properties ensure excellent engine protection over a wide temperature range.
- Group 2 Hydrocracked Base Oils offer superior engine protection, reduced wear, and improved fuel economy.
- Advanced additive package ensures engine cleanliness and sludge control.

PACK SIZES AVAILABLE

1L - 5L - 20L - 60L - 200L - 1000L IBC

SPECIFICATIONS

API SP/ CF

TYPICAL CHARACTERISTICS

EXPERT GT 15W-40	UNITS	VALUES
VISCOSITY	cSt @ 40°C	113.1
	cSt @ 100°C	14.9
SPECIFIC GRAVITY	@ 15°C	0.878
VISCOSITY INDEX		136
POUR POINT	°C	-27
FLASH POINT	°C	220

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.

* Vertex is a registered trademark of Vertex Lubricants NZ Ltd.

Vertex Lubricants Tel: 0800 353 645 Email: info@vertexlubricants.co.nz www.vertexlubricants.co.nz