



EXPERT VW 5W-30

PRODUCT DESCRIPTION

Vertex Expert VW 5W-30 is a premium quality "Mid SAPS" passenger car lubricant specifically formulated for clean earth emission reductions. The product is blended with high quality Polyalphaolefins (PAO) base fluid and high-performance additives that meet the requirements of ACEA C3, MB-229.51 and VW 504.00 / 507.00. It is suitable for use in the widest range of modern Gasoline and Diesel Passenger Cars and light-duty vehicles. Vertex Expert VW 5W-30 provides high temperature protection, exceeding the standards of Mercedes Benz, BMW, Porsche, and VW. The product is designed to work with vehicles fitted with after-exhaust treatment systems and can be used in almost all European vehicles requiring the highest standard of fully synthetic engine oil.

APPLICATIONS & BENEFITS

- Formulated for use in High Performance vehicles fitted with after-exhaust treatment systems.
- Polyalphaolefins (PAO) synthetic base stocks ensures the highest possible engine protection.
- Shear stable Viscosity Modifiers guarantee the product stays within grade throughout the service interval.
- The product can be used in the widest range of modern high-performance gasoline and diesel engines.

PACK SIZES AVAILABLE

1L - 5L - 20L - 60L - 200L - 1000L IBC

SPECIFICATIONS

- API SN
- ACEA C3
- BMW LL-04
- MB 229.51

- Porsche C30
- VW 504.00
- VW 507.00
- TL 52195

TYPICAL CHARACTERISTICS

EXPERT VW 5W-30	UNITS	VALUES
VISCOSITY	cSt @ 40°C	67.9
	cSt @ 100°C	11.8
SPECIFIC GRAVITY	@ 15°C	0.849
VISCOSITY INDEX		170
POUR POINT	°C	-42
FLASH POINT	°C	214
CCS, cP		4820
TBN, mg KOH/g		7.9





ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.