



MAGNA DD 40

PRODUCT DESCRIPTION

Magna DD 40 Diesel Engine Oil is a monograde SAE 40 providing premium quality service in both two stroke and four stroke diesel and gasoline engines. It is specially formulated for heavy-duty diesel engines found in both on-highway and off-highway vehicles and equipment. Magna DD 40 Diesel Engine Oil is specially formulated with advanced dispersant technology to resist oil thickening caused by soot generated through the engine's combustion cycle. The dispersant minimizes sludge formation maintaining engine cleanliness and reducing abrasive wear. Magna DD 40 Diesel Engine Oil is recommended for use in diesel trucks, heavy-duty construction equipment, oil field engines, farm vehicles and some passenger diesel cars.

APPLICATIONS & BENEFITS

- Monograde formulation suitable for older diesel engines and two-stroke diesel engines.
- Suitable for use in stationery engines such as continual use diesel generators that typically operate for extended periods at high temperatures.
- Suitable for use in hydraulics and transmission systems requiring a monograde 40 engine oil.

PACK SIZES AVAILABLE

20L - 200L

SPECIFICATIONS

- API CF-2
- API CF/SF

TYPICAL CHARACTERISTICS

MAGNA DD 40	UNITS	VALUES
VISCOSITY	cSt @ 40°C	133
	cSt @ 100°C	14.5
SPECIFIC GRAVITY	@ 15°C	0.883
VISCOSITY INDEX		108
POUR POINT	°C	-15
FLASH POINT	°C	234
TBN, mg KOH/g		7.9

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.

© Vertex is a registered trademark of Lubricants NZ Ltd.

Vertex Lubricants Tel: 0800 353 645 Email: vertexoli.co.nz www.vertexlubricants.co.nz





ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.

Vertex Lubricants Tel: 0800 353 645 Email: Vertex Lubricants www.vertexlubricants.co.nz