

AIR TOOL OIL 32

PRODUCT DESCRIPTION

Vertex Air Tool Oil 32 is a blend of highly refined base oils and special additives which produce a superior lubricant for pneumatic equipment. The naturally high viscosity index provides optimum lubrication for both low start-up temperatures and optimal performance during high operational temperatures. Extreme pressure additives prevent wear and withstand the high loads commonly encountered in complex pneumatic systems.

APPLICATIONS & BENEFITS

- Vertex Air Tool Oil is suitable for use in heavy duty pneumatic systems operating continuously under extreme conditions.
- Extreme pressure additives extend equipment life.
- Suitable for use in a wide range of temperatures.

PACK SIZES AVAILABLE

1L

SPECIFICATIONS

- Suitable for most pneumatic equipment requiring an ISO 32 Air Tool Oil

ROCK DRILL 100	UNITS	VALUES
VISCOSITY	cSt @ 40°C	32.1
	cSt @ 100°C	5.45
SPECIFIC GRAVITY	@ 15°C	0.859
VISCOSITY INDEX		104
POUR POINT	°C	-18
FLASH POINT	°C	210

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.