

ROCK DRILL 220

PRODUCT DESCRIPTION

Vertex Rock Drill 220 oil is a blend of highly refined base oils and special additives which produce a superior lubricant for air powered equipment. The naturally high viscosity index provides optimum lubrication for both low start-up temperatures and optimal performance during high operational temperatures. Extreme pressure additives prevent wear and withstand the high loads commonly encountered in rock drills, jackhammers, and other pneumatic equipment.

APPLICATIONS & BENEFITS

- Vertex Rock Drill 220 is suitable for use in heavy duty pneumatic equipment operating under extreme conditions.
- Extreme pressure additives extend equipment life.
- Suitable for use in a wide range of temperatures.

PACK SIZES AVAILABLE

20L - 200L

SPECIFICATIONS

- Ingersoll-Rand
- Gardner- Denver
- Sullivan
- Most Heavy-Duty pneumatic equipment requiring an ISO 220 Rock Drill Oil

TYPICAL CHARACTERISTICS

ROCK DRILL 150	UNITS	VALUES
VISCOSITY	cSt @ 40°C	220
	cSt @ 100°C	19.5
SPECIFIC GRAVITY	@ 15°C	0.896
VISCOSITY INDEX		101
POUR POINT	°C	-9
FLASH POINT	°C	252

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.