

MOTO 4T MAX 10W-40

PRODUCT DESCRIPTION

Moto 4T max 10W-40 motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. The product contains a balanced blend of a specially selected synthetic base, high viscosity index base stocks and a special proprietary additive package. Moto 4T max 10W-40 motorcycle oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity. Advanced additives provide powerful detergents to ensure the highest engine cleanliness and deposit control. Moto 4T max 10W-40 can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

APPLICATIONS & BENEFITS

- Protects engine under severe operating conditions.
- Enhanced piston and engine cleanliness.
- Prevents harmful deposit formation on vital engine parts.
- Provides wet clutch durability.
- Prolong hardware and engine life.

PACK SIZES AVAILABLE

1L - 5L - 20L - 200L

SPECIFICATIONS

- API SJ
- JASO MA2

TYPICAL CHARACTERISTICS

MOTO 4T MAX 10W-40	UNITS	VALUES
VISCOSITY	cSt @ 40°C	94.2
	cSt @ 100°C	14.2
SPECIFIC GRAVITY	@ 15°C	0.864
VISCOSITY INDEX		155
POUR POINT	°C	-33
FLASH POINT	°C	215
TBN, mg KOH/g		7.5

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.