

### TRANSMATIC CVT FE

#### PRODUCT DESCRIPTION

Transmatic CVT FE is a Synthetic Transmission Fluid blended with high-performance synthetic base oils and high-performance additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents. Transmatic CVT FE is a multi-vehicle automatic transmission fluid which provides suitable performance in a wide-range of CVT-equipped passenger vehicles which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance in modern CVT transmissions.

#### APPLICATIONS & BENEFITS

- High performance additives and synthetic base stocks capable of servicing a wide range of CVT transmissions.
- Provides excellent friction, oxidation, and thermal stability.
- Outstanding anti-wear properties and oil film thickness.
- Excellent shear stability for consistent shift.
- Compatible with a wide range of seals.

#### PACK SIZES AVAILABLE

5L - 20L - 200L

#### SPECIFICATIONS

- |                                    |  |                                     |
|------------------------------------|--|-------------------------------------|
| • AUDI / VW P/N G 052 180 (-A2)    | • MITSUBISHI DIAMOND GREEN CVTF-J4         | • SUBARU e-CVTF                     |
| • AUDI / VW P/N G 052 516 A2       | • NISSAN NS-1                              | • SUBARU HIGH TORQUE P/N K0421Y0700 |
| • DAIHATSU AMMIX CVTF-DFE          | • NISSAN NS-2                              | • SUZUKI CVT FLUID GREEN 1          |
| • DAIHATSU AMMIX CVTF-DTC          | • NISSAN NS-3                              | • SUZUKI CVT FLUID GREEN 2          |
| • DODGE / JEEP NS-2                | • RENAULT ELF MATIC                        | • SUZUKI CVTF 3320                  |
| • FCA CVTF+4 P/N 05191184AA        | • SHELL GREEN 1V                           | • SUZUKI NS-2                       |
| • GM CVTF I-GREEN2                 | • SUBARU LINEARTRONIC CVTF                 | • TOYOTA / LEXUS FE                 |
| • GM CVT P/N 19260800              | • SUBARU LINEARTRONIC CVTF-II;             | • TOYOTA / LEXUS TC                 |
| • HONDA HCF-2 P/N 08200-HCF2       | P/N K0425Y0711                             |                                     |
| • MAZDA CVTF 3320                  | • SUBARU LINEARTRONIC CV-30 P/N K0425Y0710 |                                     |
| • MITSUBISHI DIAMOND GREEN CVTF-J1 |  |                                     |

#### TYPICAL CHARACTERISTICS

TRANSMATIC CVT FE	UNITS	VALUES
VISCOSITY	cSt @ 40°C	35.99
	cSt @ 100°C	7.21
SPECIFIC GRAVITY	@ 15°C	0.8540
VISCOSITY INDEX		169
POUR POINT	°C	-45
FLASH POINT	°C	190
BROOKFIELD VISCOSITY	@ -40°C	14330

### ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.