

## AQUA 4T 10W-40

## PRODUCT DESCRIPTION

Vertex Aqua 4T 10W-40 is a premium quality, semi synthetic petrol engine oil containing specialised rust inhibitors and anti-wear additives for optimum engine protection in marine environments. Vertex Aqua 4T 10W-40 meets the requirements of NMMA FC-W<sup>®</sup> industry specification, specifically designed for marine applications. Vertex Aqua 4T 10W-40 is designed for use in all types of petrol four stroke outboard engines where SAE 10W-40 and SAE 15W-40 oils are specified including: Honda, Johnson, Nissan, Suzuki, Tohatsu, Yamaha and other manufacturers. Vertex Aqua 4T 10W-40 is also ideal for use in personal watercraft / inboard & stern drive petrol engines that require a 10W-40 viscosity grade such as: Honda, Kawasaki, Sea-Doo, Yamaha, VM and other manufacturers. Vertex Aqua 4T 10W-40 may be used in modern petrol-engine cars that require API SL oils or where an ILSAC GF-3 is specified. Not suitable for Diesel fuelled engines which should use the appropriate Vertex diesel oil.

## APPLICATIONS &amp; BENEFITS

- Vertex Aqua 4T 10W-40 protects against rust even in marine saltwater environments.
- Meets NMMA (National Marine Manufacturers Association) FC-W<sup>®</sup> requirements.
- Combines the benefits of fast oil flow at start up with superior high temperature wear protection.
- Longer engine life by protecting against wear.
- Vertex Aqua 4T 10W-40 contains full zinc for maximum wear protection.

## PACK SIZES AVAILABLE

1L - 5L - 20L - 60L - 200L - 1000L IBC

## SPECIFICATIONS

- NMMA FC-W
- API SL
- JASO MA
- ILSAC GF-3

## TYPICAL CHARACTERISTICS

| AQUA 4T 10W-40  | UNITS       | VALUES |
|-----------------|-------------|--------|
| VISCOSITY       | cSt @ 40°C  | 88     |
|                 | cSt @ 100°C | 13.3   |
| VISCOSITY INDEX |             | 153    |
| ZINC            | % mass      | 0.132  |
| PHOSPHOROUS     | % mass      | 0.121  |
| SULPHATED ASH   | % mass      | 0.910  |
| TBN, mg KOH/g   |             | 7.4    |

### ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.

\* Vertex is a registered trademark of Vertex Lubricants NZ Ltd.