

PRODUCT DESCRIPTION

Aqua 2T Two Stroke Engine Oil has been formulated for Outboard 2T Water Cooled Two-Cycle engines and meets the requirements of the National Marine Manufacturer's Association (NMMA) TC-W3 specification. It contains premium quality lubricating base stocks plus ashless additives and increased detergency to give the best quality protection in all types of high performance two cycle engines calling for TC-W, TC-W2 and TC-W3 oils. Aqua 2T also exceeds the performance requirements of the API service classification TC two-cycle engine which is commonly recommended for air-cooled two-cycle engine oils. Aqua 2T Two-Cycle Motor Oil mixes easily with gasoline and flows through injectors even at very low temperature. The product is recommended for use in all outboard marine engines including Evinrude, Johnson, Mercury, Suzuki, and Yamaha.

APPLICATIONS & BENEFITS

- Meets TC-W3 specification for high performance two stroke marine engines.
- Ashless formulation provides high performance operation under the most arduous operations.
- Advanced additives prevent spark plug fouling and optimum engine performance.
- Suitable for direct oil injection systems.
- Suitable for use in engines fitted with after exhaust treatment systems.

PACK SIZES AVAILABLE

1L - 5L - 20L - 200L

SPECIFICATIONS

NMMA TC-W/ TC-W2/ TC-W3 classifications

TYPICAL CHARACTERISTICS

AQUA 2T TCW3	UNITS	VALUES
VISCOSITY	cSt @ 40°C	42.4
	cSt @ 100°C	7.1
SPECIFIC GRAVITY	@ 15°C	0.872
VISCOSITY INDEX		128
POUR POINT	°C	-21
FLASH POINT	°C	93

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.

* Vertex is a registered trademark of Vertex Lubricants NZ Ltd.