

LOG MARKER

PRODUCT DESCRIPTION

Vertex Log Marker is a high-grade concentrated spray containing high purity pigments. The product is available in a wide range of colours. Designed to spray Upside Down for ease of use and accurate line marking. Vertex Ground Marker is suitable for multi-purpose applications as well as a traditional log marker. Vertex Log Marker is designed for Identification marking of trees, logs, and lumber. Formulated to provide high visibility marks that withstand the critical test of long-term exposure. The product can be used in all weather conditions and is suitable for application on saturated logs. The product is fast drying and has exceptional adhesion properties to wet and dry surfaces. The product has a guaranteed minimum shelf life of a year. Vertex Log Marker aerosols contain no lead or other heavy metal and are free of chlorofluorocarbons (CFCs) or other ozone-depleting compounds.

APPLICATIONS & BENEFITS

- Suitable for marking in severe weather and environments.
- Film unaffected by water saturation.
- High-visibility markings on hardwood or softwood logs
- Creates a strong visual impact to attract attention at a distance.
- Controlled penetration rate gives uniform marks on smooth and rough surfaces.
- Special resin and pigment package provides long term durability and resistance to weathering from sunlight or moisture.
- The specially balanced formula reduces settling, promotes total product exhaustion, and the high solids content means your product lasts longer than similar products on the market.
- Exact matched to exceed industry colour, durability, and performance needs.
- Excellent exterior durability through use of high-performance resins and pigments.
- Fast drying, exceptional adhesion to wet and dry surfaces. Guaranteed minimum shelf life of a year.
- Our aerosols contain no lead or other heavy metal, no chlorofluorocarbons (CFCs) or other ozone-depleting compounds.

PACK SIZES AVAILABLE

400 ml Aerosol (UN Blue - Red - Black - Yellow - Green - Fluro Pink - Waterproof White Properties)

ADDITIONAL INFORMATION

Directions for Use

Shake can until agitator ball is moving freely to ensure content is thoroughly mixed. Apply with smooth even strokes to surface holding can approximately 20cm from surface until desired coverage is achieved.

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 17 July 2023.